



# Instruction Guide


*for the  
Speedy Stitcher  
Sewing Awl*



## AN INDISPENSABLE TOOL FOR SEWING

- AWNINGS
- SAILS
- TENTS
- AUTO TOPS
- UPHOLSTERY
- SADDLES
- SHOES
- HANDBAGS
- ALL TYPES OF SPORTING EQUIPMENT






## TO SET UP


- Unscrew chuck lock to find needles
- Pull end of thread from bobbin through hole in handle
- Loop thread around tension post as shown in Detail 'A'.
- Continue thread along handle groove and through ferrule hole as illustrated.
- Place needle in threaded post making sure that grooves in needle and threaded post are in alignment with each other.
- **Pass thread through eye of needle, then through chuck lock as shown.**
- Screw chuck lock onto threaded post and tighten securely by hand only.

1




## DETAIL 'A'

- When looping thread around tension post, be sure to pass it under the thread coming from hole in handle as shown above, otherwise it will not feed freely.




## TO STITCH







- Push needle through material and draw out enough thread to do the length of work involved, plus about 3" more.
- Draw thread through material so that the full length of thread is pulled through the hole in which the needle rests.
- Hold thread in position and pull needle back through the material and start it through a second hole.



- Push needle as far as it will go, then draw back enough so that the thread forms a loop as shown.
- Pass all of the thread through this loop.



- While holding thread taut in one hand, draw needle out with other hand. This forms a lock-stitch in the material.
  - Draw equally hard on the Awl and the loose end of the thread.
  - Before taking another stitch, release more thread between the needle and the material to allow you to move the awl back and start the next hole.
  - Continue same procedure until finished.
- After you have finished your stitching, use the following procedure to tie off the thread. On your last stitch, instead of passing thread through the loop, grasp loop and pull out about 3 inches of thread. Cut thread. Then pull Awl and needle out of material. Now you have both ends of thread on same side of material for tying off. Use square knot.

Supplies for the Speedy Stitcher	Needles
<p data-bbox="125 144 596 179" style="text-align: center;">Waxed Polyester Thread (Tan)</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p data-bbox="68 291 265 351">No. 140 Coarse No. 160 Fine</p>  <p data-bbox="101 477 249 501">30 Yd. Skein</p> </div> <div style="text-align: center;"> <p data-bbox="291 246 487 270">No. 150 Coarse</p>  <p data-bbox="298 564 462 588">180 Yd. Tube</p> </div> <div style="text-align: center;"> <p data-bbox="522 246 679 270">No. 170 Fine</p>  <p data-bbox="513 564 677 588">180 Yd. Tube</p> </div> </div>	<p data-bbox="739 137 886 161">No.130 - #4</p>  <p data-bbox="778 239 897 295">No. 130A -#8S</p>   <p data-bbox="739 645 930 669">No. 130B - #8C</p>

**IMPORTANT** – Fine sewing requires FINE THREAD and the 130-#4 NEEDLE. Both are pictured above. If these supplies are not available from your dealer, we will be pleased to help you locate a supplier. Visit [www.speedystitcher.com](http://www.speedystitcher.com) or email [info@speedystitcher.com](mailto:info@speedystitcher.com).

Manufactured in the U.S.A by:

Silver Creek  
Leather Co.

5035 Keystone Blvd. • Jeffersonville, IN • 47130